



SLIDE COLD

Non-insulated system for light sliding elements







PERFORMANCE LEVEL

AIR TRANSMISSION	NBN EN 12207	Classe 3
WATERTIGHTNESS	NBN EN 12208	Classe 5A
RESISTANCE TO WIND	NBN EN 12210	Classe C3
BURGLARPROOF	NEN 5096 & ENV 1627	RC2

APPLICATIONS

Non-insulated sliding windows separating the terrace. Different variations possible: 2-, 3-, 4-, and 6-part

TECHNICAL FEATURES

- Min. visible width: frame: 54mm / sash: 69mm
- Installation depth frame[.] Monorail: 47.5mm

Duorail: 51mm 3-rail: 99mm

32mm

- sash:
- Glass thickness: 6-9mm & 20-24mm
- Maximum sash weight: 160kg



100% MADE IN BELGIUM



Aliplast develops aluminium profiles tailored to current housing needs. Everything happens under one roof: from drawing to extrusion, powder coating, insulation and transport to the Aliplast

distributors. The distributors produce and install the finished windows in your building project.

25-YEAR COLOUR GUARANTEE



Aliplast gives a 25-year guarantee on 50 current colours. The Qualicoat Seaside quality label ensures that your paint colour is extra protected against

aggressive environments (exhaust fumes, salty sea air, etc.). You enjoy a 15-year guarantee on all other colours. Peace of mind for the future.

DURABLE PRODUCT



Aluminium is a durable product because it has a long lifespan. Moreover, the material is fully recyclable and can therefore be

completely reused without compromising on quality. Aliplast mainly uses recycled aluminium billets for architectural systems. This aluminium is "Green Metal". It has a positive impact on people and the environment.